



RP-327 - I

Thermal Printer

- Fashion appearance
- With high speed, excellent stability and durability
- Paper detection by transmission type, accurately and rapidly
- Imported thermal printer head, printing clearly

Smart Interface :



Specification

Variant I : USE

Media Type	Direct thermal printing
Resolution	203dpi
Print Width	72mm or 48mm
Printing speed	250 mm/s
Dots per Line	576 or 384
Character Set	"PC347 (Standard Europe) / Katakana/PC850 (Multilingual) /PC860(Portugal)/East Europe/Iran/WPC1252/PC866(Cyrillic#2) /PC852(Latin2)/PC857/IranII/Latvian / Arabic / PT151 (1251)"
1D Barcode	UPC-A/UPC-E/JAN13(EAN13) / JAN8 (EAN8) / Code39/ ITF/ Codabar/Code93/Code128
2D Barcode	QR CODE / PDF417
Fonts	ASCII A: 12×24, B: 9×17, Chinese: 24×24
Characters per Line	Font A: 48, Font B: 64, Chinese: 24
Paper Width	79.5 ± 0.5 mm
Paper Roll Diameter	Φ80 mm
Paper Thickness	0.06–0.08 mm
Paper Loading	Easy loading
Auto Cutter Life	1.5 million cuts
Print Head Life	150 KM
Interface	Variant - I USB / Variant -II WBUSE
Driver Support	Windows/Linux/Mac/JavaPOS/OPOS
SDK Support	Windows/Android/iOS

Certifications



V1.2_26112025

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093
 Tel : +91 80 4078 2700 | Mob : +91 9535432110
 Email : marketing@posiflexindia.com | www.posiflexindia.com

Authorized Distributor / Reseller

Specification	Variant I : USE
Command Set	ESC/POS/OPOS
Cash Drawer Control	DC 24V, 1A
Power Supply	DC 24V, 2.5A
Dimensions (L×W×H)	191×140×143 mm
Weight	1.01 KG
Operating Temperature	0–45°C
Storage Temperature	-20–60°C
Humidity (Operating)	10–90% (non-condensing)
Certifications	3C, CE, FCCID, ROHS, BIS, REACH
Special Features	Waterproof, insect-proof, oil-proof, Ring light alarm, ≥90db sound cavity, Wall mountable, Paper removal detection

Certifications



V1.2_26112025

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093

Tel : +91 80 4078 2700 | Mob : +91 9535432110

Email : marketing@posiflexindia.com | www.posiflexindia.com

Authorized Distributor / Reseller