



SRP - 352 plus VK

Direct Thermal

- Premium 3-inch (80 mm) Thermal Receipt Printer series
- Equipped with durable mechanical switches for reliable performance
- Supports Blue Receipt printing for eco-friendly use
- High print speed: up to 370 mm/sec
- Resolution: 203 dpi for sharp and clear prints
- Model: SRP-352plusVK
- Offers wireless connectivity options for flexible operations

Specification

SRP - 352 plus VK

Print Characteristics	
Print Method	Direct Thermal
Print Speed	Up to 370 mm/sec
Print Resolution	203 dpi
Print Width	Up to 72 mm
Sensor	Paper End, Paper Near End, Cover Open, Visibility Intelligence Sensor
Media Characteristics	
Media Type	Receipt
Media Width	80 mm Optional 58 mm
Media Roll Diameter	Up to 83 mm
Media Thickness	0.05 ~ 0.08 mm
Supply Method	Easy Paper Loading
Physical Characteristics	
Dimensions (W x D x H)	145 x 200 x 146 mm (5.70 x 7.87 x 5.74 inch)
Weight	1.6 kg (3.52 lbs.)
Electrical	EnergyStar Certified, External Power Adaptor 100-240 V AV, 50/60 Hz
Drawer Port	2 ports (Via y-type adaptor)
Performance Characteristics	
Memory	64 Mb SDRAM, 64 Mb Flash
NV Image Memory	768 Kbytes (Mono)
Receive Buffer	4 Kbytes
User Define Buffer	12 Kbytes
Interface	Standard: USB V2.0 FS + Ethernet Optional: ① USB V2.0 FS + Ethernet + Serial ② USB V2.0 FS + Ethernet + Dual Serial ③ USB V2.0 FS + Ethernet + Parallel ④ USB V2.0 FS + Ethernet + WLAN¹ ⑤ USB V2.0 FS + Ethernet + Bluetooth ⑥ USB V2.0 FS + Ethernet + Powered USB WLAN: 802.11a/b/g/n (Infrastructure, Ad-hoc, Wi-Fi Direct, SoftAP) WEP40/104, WPA1/2 (PSK, EAP)

Certifications



WPC



V1.1-28102025

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093

Tel : +91 80 4078 2700 | Mob : +91 9535432110

Email : marketing@posiflexindia.com | www.rugtek.com

Authorized Distributor / Reseller

Specification

SRP - 352 plus VK

Environment Characteristics	
Temperature	Operating: 0 ~ 40 °C (32 ~ 104 °F) Storage: -20 ~ 60 °C (-4 ~ 140 °F)
Humidity	Operating: 10 ~ 80 % RH Storage: 10 ~ 90 % RH
Software	
Emulation	BXL / POS
Driver / Utility	Windows Driver OPOS/JPOS Driver Linux/Mac CUPS Driver Virtual COM USB/Ethernet Driver Utility Program Network Auto Installer
SDK / Plugin	Android/iOS/Windows SDK Linux SDK Xamarin SDK Web Print SDK Cordova Plugin
MDM (Optional)	BIXOLON Profile Manager - XPM™, XCM™ (Windows, Android)
Fonts / Graphics / Symbologies	
Character Size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24 Characters Per Line SRP-350plusV: Font A: 42, Font B, C: 56, KOR, CHN, JPN: 21 SRP-352plusV: Font A: 48 Font B, C: 64 KOR, CHN, JPN: 24
Character Sets	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32
Graphics	Supporting user-defined fonts, graphics, formats, and logos
Barcode Symbologies	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, PDF417, QR code
Accessories	
Standard	RJ12 6pin cable Adapter (Male to Female), USB A-B Cable 1.8 m
Optional	Built-in SMPS, Vertical stand, Wall mount, Splash Proof Cover, External buzzer, B-Melodist, Powered USB (0.5/1.2 m), Serial Cable (9-9/25-9 pin), Parallel Cable

Certifications



V1.1-28102025

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093
 Tel : +91 80 4078 2700 | Mob : +91 9535432110
 Email : marketing@posiflexindia.com | www.rugtek.com

Authorized Distributor / Reseller