



SRP - E302 ESK

Direct Thermal

- 3-inch (80 mm) rugged thermal receipt printer
- Print speed: up to 220 mm/sec, resolution: 203 dpi
- Printing width: 72 mm, with integrated cutter
- Thermal printing ideal for retail and hospitality
- Connectivity: USB 2.0, Ethernet, and Serial

Specification

SRP - E302 ESK

Print Characteristics	
Print Method	Direct Thermal
Print Speed	Up to 220 mm/sec
Print Resolution	203 DPI
Print Width	Up to 72 mm
Sensor	Paper End, Cover open
Media Characteristics	
Media Type	Receipt
Media Width	80 mm Optional 58 mm
Media Roll Diameter	Up to 83 mm
Media Thickness	0.05 ~ 0.08 mm
Supply Method	Easy Paper Loading
Physical Characteristics	
Dimensions (W x D x H)	132x182.4x1258. mm(5.19 x 7.18x 5.05 inch)
Weight	1.23 Kg (2.71 lbs)
Electrical	EnergyStar Certified, External Power Adaptor 100-240 V AV, 50/60 Hz
Drawer Port	2 ports (Via y-type adaptor)
Performance Characteristics	
NV Image Memory	768 Kbytes (Mono)
Receive Buffer	4 Kbytes
User Define Buffer	12 Kbytes
Interface	Standard: USB V2.0 FS

Certifications



V1.1-28102025

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093
 Tel : +91 80 4078 2700 | Mob : +91 9535432110
 Email : marketing@posiflexindia.com | www.rugtek.com

Authorized Distributor / Reseller

Specification

SRP - E302 ESK

Environment Characteristics	
Temperature	Operating: 0 ~ 40 °C (32 ~ 104 °F) Storage: -20 ~ 60 °C (-4 ~ 140 °F)
Humidity	Operating: 10 ~ 80 % RH Storage: 10 ~ 90 % RH
Software	
Emulation	BXL / POS
Driver / Utility	Windows Driver OPOS/JPOS Driver Linux/Mac CUPS Driver Virtual COM USB driver,utility program
SDK / Plugin	Android/iOS/Windows SDK Linux SDK Xamarin SDK Web Print SDK Cordova Plugin
Application	mPrint App (Android, iOS)
MDM (Optional)	BIXOLON Profile Manager - XPM™, XCM™ (Windows, Android)
Fonts / Graphics / Symbolologies	
Character Size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24, KOR, CHN, JPN: 24 x 24 Characters Per Line SRP-350plusV: Font A: 42, Font B, C: 56, KOR, CHN, JPN: 21 SRP-352plusV: Font A: 48 Font B, C: 64 KOR, CHN, JPN: 24
Character Sets	Alphanumeric: 95 Extended Graphics: 128 x 35 page International: 32
Graphics	Supporting user-defined fonts, graphics, formats, and logos
Barcode Symbolologies	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, PDF417, QR code
Accessories	
Standard	USB A-B Cable 1.8 m
Optional	External buzzer

Certifications



V1.1-28102025

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093
Tel : +91 80 4078 2700 | Mob : +91 9535432110
Email : marketing@posiflexindia.com | www.rugtek.com

Authorized Distributor / Reseller