

Thermal Ticket Printer



Windows



Android



Linux



RP 76x

High Performance Compact Intelligent Table Top Thermal Ticket Printer

Salient Features

- Designed to meet the on demand ticket printing with full feature to control & monitor the ticket printing.
- Auto Load & adjust upon loading of paper to print position.
- Supports multiple ticket size.
- Status monitoring of printer through special commands sent via I/O (features like paper out/cover open/offline/online /ready/print success status).
- Printer stop printing when cover open.
- Clears buffer memory when cover open or power off.
- Supports multiple ticket length with black mark as end of ticket.
- Supports print from 2nd line when new or reload of media roll, cover open, printer on/off condition.

RP 76x

Print Specifications	Print Method: Direct Thermal (outer coating support), Resolution: 203dpi, Color: Black Print Speed: Max 127mm/sec, (150mm/sec in continues paper feed). Print immediately on print command RAM: 8MB, Flash: 4MB(expand memory 8MB realizable).
Media Specifications	Print Width: 26.7-120mm, Print Width/Length: Max W 104mm /L upto 200mm, Paper Thickness: 60-120GSM Paper-cut width/condition: Max 120mm/Leaves for 2+0.5mm, No Cut/Partial Cut/ Full Cut Paper Roll: Supports media roll Dia upto 150mm(Prints approx 500 tickets), Optional external stand for larger media roll above 150mm
Media Sensor	Continuous Receipt, Label Gap & black Mark Sensor (Supports max 102mm width, height 2~4mm), cover open, paper present
Button / Cutter Spec	Button: Power On & Status Paper-cutting time: Up to 600 milliseconds/per cycle Paper-cutting frequency: Fastest 60 times per minute, MTBF: Printing 5m lines or 100KM length/cutting-1m times]
Interface	Auto Support USB+Serial, USB + Parallal / Serial Optional BT & WiFi. Factory Default baud rate can be set.
Command/OS Support	Full Support of ESC/POS, CPCL/WinXp, Win7/10, Android, Linux
Barcode /Language / Font Support	Support 1D, 2D & QR Barcode, Default Hindi & English, other Language Support on request. Supports Graphics printing (CR disable feature incorporated) 12x24 fonts & special Railway Fonts to print all Vowel characters in Italic & option to customise the printer firmware with any special fonts."
Power	Specification: DC 24V/2.5A , Power Adaptor AC support 90v~240v Peak Value: 8A
Dimensions(LxWxH) /Weight	238mm(L)*170mm(W)*168mm(H)/1.4kg
Environment Parameters	Operating Temperature (°C): 0°~60° Humidity : 10~90% RH (Non Condensing) Storage Temperature: -10°C~60°C
Accessories	Adaptor, Communication Cable, Power Cable, User Manual, In-built paper Guide to align receipt printer

Solutions



Utility
Transport Ticket



Multiplex Ticketing



Lottery



Retail Shops



Quick Service
Restaurant



Food Delivery

RUGTEK

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD

7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavara, Bengaluru, Karnataka 560093
Tel : 080-40782700 E-mail : marketing@posiflexindia.com
Mob : +91 9535 432110 www.rugtek.com

Authorized Distributor / Reseller