



RP-327 - I / II

Thermal Kitchen Receipt Printer

- Three proof paint, dedicated waterproof cover design: waterproof and dustproof structures
- Flash LED light and built-in high volume kitchen alarm: designed specifically for noisy kitchen environments
- Paper take-out sensors: reduce the hassle of missing orders
- 250mm/s High printing speed, automatic paper cutting
- Supports two applications, flat and wall mounted: meeting different kitchen needs



Specification

RP 327 - I Variant : USE / RP 327 - II Variant : WBUE

Media Type	Thermal Transfer	
Resolution	203dpi	
Print Width	72mm or 48mm (58mm compatible)	
Printing speed	250 mm/s	
Dots per Line	576 or 384	
Character Set	GB18030	
Fonts	ASCII A: 12×24, B: 9×17, Chinese: 24×24	
Characters per Line	Font A: 48, Font B: 64, Chinese: 24	
Paper Width	79.5 ± 0.5 mm	
Paper Roll Diameter	Φ80 mm	
Paper Thickness	0.06–0.08 mm	
Paper Loading	Easy loading	
Auto Cutter Life	1.5 million cuts	
Print Head Life	150 KM	
Interface	USB/Serial/Ethernet	WIFI/bluetooth/USB/Ethernet
Driver Support	Windows/Linux/Mac/JavaPOS/OPOS	
SDK Support	Windows/Android/iOS	
Command Set	ESC/POS/OPOS	
Cash Drawer Control	DC 24V, 1A	
Power Supply	DC 24V, 2.5A	
Dimensions (L×W×H)	191×140×143 mm	
Weight	1.01 KG	
Operating Temperature	0–45°C	
Storage Temperature	-20–60°C	
Humidity (Operating)	10–90% (except paper roll)	
Certifications	3C, CE, FCCID, ROHS, BIS, REACH	
Special Features	Waterproof, insect-proof, oil-proof, Ring light alarm, ≥90db sound cavity, Wall mountable, Paper removal detection	

Certifications



V1.3_22012026

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093

Tel : +91 80 4078 2700 | Mob : +91 9535432110

Email : marketing@posiflexindia.com | www.posiflexindia.com

Authorized Distributor / Reseller