



# RP-82

## Compact Printer



### Specification

<b>Print</b>	
Printing Method	Thermal Line
Printing Speed	200mm/s
Resolution	203dpi
Effective Printing Width	72mm & 48mm
Printing Setting	Support adjustment for the header margin, line space, receipt width and barcode height
RAM	96KB
FLASH	2MB
<b>Character</b>	
Character Set	ANK,GB18030(Chinese)
Print Font	ANK: 12 x24,9x17, Chinese: 24 x 24
Character per Line	48-font A/64-font B
<b>Paper Spec</b>	48-80 GSM, with thicknesses ranging from 0.052mm to 0.09mm
Paper Type	Thermal paper
Paper Width	80mm
Paper Roll Diameter	Max: 80.0mm
<b>Paper Supply Method</b>	Drop-in paper load
<b>Reliability</b>	
MCBF	60 million lines
TPH	100km
<b>Barcodes</b>	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODEBAR, CODE93, CODE128
<b>Emulation</b>	ESC/POS
<b>Driver</b>	Win10, Win 11, Win IOT, iOS, Android, Linux
<b>Sensor</b>	Paper End Sensor, Paper Near End Sensor(Optional)
<b>Drawer Port</b>	RJ11
<b>Interface</b>	USB+LAN
<b>Network</b>	
Wire	TCP/IP Ethernet interface (10M/100M)
Power Supply (Adapter)	AC100 ~240V(± 10%) DC 24V, 2.5A
<b>Auto cutter</b>	
Type	Straight Knife
Life	1.5 million
<b>Physical</b>	
Printer Dimension (WxLxH)	156*125*120mm
Environment parameters:	Working temperature: -20℃-70℃ Working humidity: 0℃-40℃ Storing temperature: 5%-95% Storing humidity:20%-85%
Remarks	3PCS Orange light Normal: The light on Abnormal: The light flashes
Applications:	Restaurant, Department Store, Kitchen, Convenience Store, Specialty Retail, Super market